



REV.	ECN_NO.	DESCRIPTION	DRWN	APPD.	DATE
REV	ECN_NO.	DESCRIPTION	DR.	APPD.	DATE

SPEC:  
 Current Rating: 3Amps  
 Insulator Resistance: 5000mΩ Min  
 Dielectric Withstanding: AC 500V  
 Operating Temperature: -40° to+105°  
 Contact Material: Copper alloy T=0.25  
 Insulator Material: Polyester, UL 94V-0 LCP  
 Finish :  
 Gold/tin plating on contact area  
 100u" min. Tin-Lead Plating on soldertails  
 50u" min. nickel under plating over all tin,  
 Max. Processing Temp:  
 230C° for 30-60seconds(260C° for 10 secinds)  
 MARK\*\*DIMENSION MUST BE CHECKED BY QC.

Table:

PRODUCT NO.	ITEM	PART NO.	PART NAME	Q' TY	Material
ST12070101T	1	PS00010120	CONTACT	7	C2680R-H, GOLD FLASH
	2	PS00095520	定位片	2	C2680R-H, TIN 100U"
	3	PPO072BK10	HOUSING	1	LCP+30%GF, BLACK
ST12070601T	1	PS00010620	CONTACT	7	C2680R-H, GOLD 15U"
ST12070201T	2	PS00010220	CONTACT	7	C2680R-H, GOLD 30U"

UNITS mm	SCALE SCALE	REV. REV.	SHEET PAGE	深圳市连欣科技有限公司 TITLE SATA 7P 三面全包 卧式 SMT	
GENERAL TOLERANCE 0. 0.0 0.00 0'. 0.0'		DATE D_DATE	DR. DESIGNER	CHK.	MAT'L MATERIAL
		APPD.	DWG.NO. DWG_NO.	C	FINISH FINISH
				PART NO. XUTS-0727-0332	SIZE A4