



P. C. B. LAYOUT

NOTE:

1. MATERIAL:

- a. HOUSING:PBT GLASS FIBRE UL94 V-0
- b. CONTACT:BRASS T=0.25mm
(SURFACE PLATING: Au1u" + Sn80-100u" + Ni60u")
- c. SHEEL:BRASS T=0.3mm IRON T=0.3mm
(SURFACE PLATING: Cu80-100u" Ni80u"-100u")

2. ELECTRIC:

- a. CONTACT RESISTANCE:30 MILLIOHMS MAX
- b. INSULATION RESISTANCE:1000 MEGA OHMS MIN
- c. DIELECTNIC VOLTAGE:500v AC ONE MIN LEVEL
- d. OPERATING TEMPERATURE:-55° -85°

L&X 深圳市连欣科技有限公司

TOLERANCE: X.X ±0.30 X.XX ±0.25 X.XXX ±0.15 X.' ±2' X.X' ±0.5'	DRAWN BY : 陈一鸣	DATE : 2014-02-23	PART NAME: USB BF 90° DIP	
	CHECKED BY: 马跃	DATE : 2014-02-23	PART NO. XUBF-0214-0105	
UNIT: mm [inch] SCALE:1:1 SIZE: A4	APPROVED BY: 邱国夷	DATE : 2014-02-23	DRAW NO: HYC-USB14020105	
			SHEET NO. 1 OF 1	