



- Specification:
1. Rated voltage and current: 1.5A at 250V AC minimum.
  2. Dielectric withstanding voltage: 500V AC/1 minute without breakdown.
  3. Contact resistance: Before life test 30m ohm max, After life test 50m ohm max.
  4. Insulation resistance: 1000M ohm min.
  5. Insertion force: 35 Newtons maximum.
  6. Extraction force: 10 Newtons minimum.
  7. Solderability: Terminal shall be immersed in flux before text, Then dip in molten solder for 5±0.5 sec. At 245±5°C.

3	Shell	1	Brass	T=0.30mm	80~120u"Nickel Plated
2	Contact	4	Brass	T=0.25mm	Contact area:0.8~1.2u"Gold Plated over 40u"Nickel min. Solder area:80~120u"Tin Plated over 40u"Nickel min.
1	Housing	1	PA6T	UL 94-V0	Black/Ivory△
No.	Name	Q'ty	Material	Remarks&Thickness	Finish

SCALE: AS SHOWN	UNIT: mm	L&X 深圳市连欣科技有限公司
DRAWN PEARL	06/09/08	DRAWN NAME:
CHECKED <i>Cheny</i>	06/10/08	USB 2.0 AF 高温贴片式卷边
APPROVED <i>Joe</i>	06/10/08	PRODUCT NO. XUBF-0410-08
SIZE A4	REV. B	FILE NAME: XUBF-0410-08